



ESTD. 1942

SATAKE

SAVCO SALES PVT. LTD.

Thickness Grader : Model No WS600AK(2)



DESCRIPTION

The Satake Thickness Grader WS was developed for the most efficient separation of broken and immature kernels from rice and wheat. The screens are selectable from a wide range of available slot sizes.

FEATURES

➔ Compact Design:

A total of six octagonal screens are fitted within the compact body. Each screen is made of corrugated steel plate with slots at regular intervals, and is light in weight. The changeover of one size of screen to another can be done quickly and easily by a single operator.

➔ Easy Maintenance:

An anti-clogging device is employed and ensures the screen slots are maintained clear all the time. It is equipped with a dust suction port to allow removal of aspirated dust and sand. A removable bottom hopper allows easy access for maintenance.

➔ Screen Variation:

There are various different screen slot widths for brown rice separation, ranging from 1.10mm to 1.95mm. Heat treated hardened screens are also available for paddy and wheat applications. Screens of 16 slot widths are available, ranging from 1.60mm to 3.00mm.

➔ Well-designed Transmission:

A geared motor with a chain drive transmission minimizes a vibration as well as transmission losses by slippage.

SPARE PARTS INFORMATION OF WS600AK(2)

MODEL

PART NO

ITEM DETAIL



2-4505-3300

SCREEN
1.10 MM-1



2-4505-3300

SCREEN 1



FC221804

FLANGE UNITE
ASPFL204



FC221805

FLANGE UNIT
ASPFL205



G552029

URETHANE RUBBER

SPARE PARTS INFORMATION OF WS600AK(2)

MODEL

PART NO

ITEM DETAIL



G5522087

ASSEMBLY SCREEN
1.20 MM



T083126

SPROCKET



TFA183003422

MOTOR 4P0.37KW
(0.5 HP)

67/B, N.S. ROAD, 2ND FLOOR, ROOM NO. 45, KOLKATA - 700001

E-mail: marketing@savcosales.com | Website: www.savcosales.com

For Any Details Contact Us -

7076500155 | (033)2262-2551/2552/2191